



International Fireproof Technology, Inc.

17528 Von Karman Ave. Irvine, CA 92614

DC315: 5 YEAR INTERIOR CONDITIONED* AIR SPACE WARRANTY

DC315 IS WARRANTED TO BE FREE OF DEFECTS IN MATERIAL AND MANUFACTURING FOR 5 YEARS, PROVIDED THE PRODUCTS ARE USED (STORED, MIXED, APPLIED AND MAINTAINED) AS DIRECTED ON APPLICATION SPECIFICATIONS. WARRANTY IS CONTINGENT ON APPLICATION IN A CONDITIONED BUILDING FOLLOWING PROCEDURES OUTLINED IN APPLICATION PROCESS OF MASTER SPECIFICATION AND APPLICATION GUIDE.

- A minimum substrate and ambient temperature of 50° F (10° C) shall be maintained prior to, during, and a minimum of 72 hours after application. If necessary for job schedule, the General Contractor shall provide enclosures and heat to maintain proper temperatures and humidity levels in the application areas.
- Ventilation shall not be less than 0.4 complete air exchanges per hour until the material is cured.
- Relative humidity shall not exceed 85% throughout the total period of application and drying for the intumescent fire resistive material.
 - Areas of ongoing High Humidity shall be top coated and applied in full accordance with the manufacturer's written instructions. Acceptable product – Sherwin Williams Promar 200 vapor barrier primer/finish or comparable as recommended by manufacturer.

NOT FOR USE ON TRAFFICABLE AREAS SUCH AS DECKS AND FLOORING. PAINT WILL NOT ALTER THE FLAMMABILITY OF THE UNDERLYING MATERIALS THEMSELVES.

NO CONSEQUENTIAL DAMAGES. SELLER SHALL NOT BE LIABLE FOR BUYER'S LOSS OF PROFITS, BUSINESS GOODWILL, OR OTHER CONSEQUENTIAL DAMAGE.

LIABILITY, IF ANY, IS LIMITED TO REPLACEMENT OF THE PRODUCT OR REFUND OF THE PURCHASE PRICE. LABOR AND OTHER MATERIAL COST ARE EXCLUDED FROM THIS LIMITED WARRANTY.

This warranty does not cover fading.

This warranty does not cover chipping, cracking, peeling, or blistering resulting from inadequate ventilation and/or improper installation techniques.

This warranty does not cover damage from installation.

This warranty does not cover coating failure from excessive expansion, contraction or movement of the substrate (as defined by industry standards).

This warranty does not cover damages from lack of proper construction or maintenance; accidents; structural defects; fire, lightning, hurricane, tornado, windstorm, earthquake, hail; catastrophic weather conditions; weather conditions; or acts of God; harmful chemicals (including cleaning compounds).

*Interior Conditioned Space- An area or room within a building being heated or cooled between 40 F (5 C) and 160 F (70 C), and provided with natural or mechanical ventilation to ensure ongoing humidity of less than 85%. For applications in Un-Conditioned spaces please contact IFTI for detailed application instructions by calling 949-975-8588.